

bersama project



Product Book

bersamaproject.com.my

Product Range

01	8pm Sofa (Broad)	pg 03
02	8pm Sofa (Calm)	pg 06
03	11pm Bedframe	pg 09
04	11pm Divan	pg 13
05	11pm Mattress	pg 17
06	Kitchen Piano	pg 20
07	First Step SPC Flooring	pg 24
08	First Step T Moulding	pg 30
09	First Step L Moulding	pg 36

10	Skirting	pg 42
11	Wainscoting	pg 48
12	Stay Longer Interior Paint	pg 52
13	Stay Longer Interior Sealer	pg 57

8pm Sofa (Broad)

BP0001B

The 8pm sofa is built on one idea:

comfort over style. Its main investment is 7-inch high-density cushions for genuine comfort, paired with a spacious frame that seats 4+ people comfortably. Cushioned edges add child-safety for family use, and the design skips extra features to keep the price low.

Specification

Width	Depth	Height
2650mm	× 1065mm	× 710mm



Installation Guide



Scan Here
for video guide

01. Unpack Carefully

Cut open the packaging with scissors (avoid knives to prevent damage.)
03. Flip onto their backs

Turn both sofa sections so they rest on their backs.
05. Flip upright again

Return both sofa pieces to their normal standing position.
07. Connect the pieces

Push the sofa sections together until you hear multiple “clicks.” (You may need help from another person or a wall for support.)
09. Assembly complete

Your sofa is ready to use!
02. Position the sofa pieces

Place both sides of the sofa where you want them.
04. Rotate the clips

Adjust the alligator clips so they face each other.
06. Align the clips

Make sure the clips on both sides line up.
08. Check the connection

If clips don’t lock, re-align and push again.
10. To disconnect

Lift one side of the sofa slightly (front and back) to release the clips.

Direction of Use

01. Use the sofa for normal sitting, resting, and household use only.
03. Place the sofa on a flat, stable, and dry surface to prevent rocking, uneven wear, or structural stress.
05. Avoid placing sharp, hot, wet, or heavy objects directly on the sofa surface.
02. Do not stand, jump, climb, or place excessive weight on the sofa, armrests, backrests, or cushions.
04. Keep the sofa away from direct sunlight, open flames, heaters, air-conditioner discharge, and excessive moisture.
06. Lift the sofa when moving it. Do not drag it, as this may damage the sofa legs, frame, flooring, or upholstery.

Routine Cleaning and Maintenance

01. Vacuum the sofa regularly using a soft brush attachment to remove dust, crumbs, and loose dirt.
03. For light cleaning, use a soft cloth slightly dampened with clean water, then allow the area to air dry completely.
05. Avoid bleach, strong solvents, abrasive cleaners, alcohol-based cleaners, and rough scrubbing tools unless specifically approved for the upholstery material.
02. Blot spills immediately with a clean, dry, absorbent cloth. Do not rub, as rubbing may spread the stain or damage the upholstery.
04. Do not soak or saturate the sofa with water or cleaning solution.
06. Always test any cleaning product on a hidden area before applying it to visible surfaces.

Upholstery-Specific Care

Upholstery Type	Care Direction
01. Fabric sofa	Vacuum regularly and clean stains promptly by blotting. Keep away from prolonged direct sunlight to reduce fading. Allow fabric to dry fully before use.

Cushion, Frame, and Fitting Care

01.

Fluff cushions regularly to help maintain shape and even wear.
03.

Do not pull or lift the sofa by the cushions, armrests, or upholstery fabric.
05.

Keep sofa legs dry and clean to prevent rust, swelling, corrosion, or floor staining, depending on the material.
02.

Avoid sitting in the same position continuously for long periods, as this may cause uneven compression.
06.

If the sofa produces unusual noise, becomes unstable, or shows structural damage, discontinue use until inspected or repaired.
04.

Check legs, screws, brackets, and fittings periodically and tighten them when necessary.

Safety Precautions

01.

Keep packaging materials, plastic bags, and small assembly parts away from children and pets.
03.

Do not place the sofa near open flames, candles, hot appliances, or other fire hazards.
05.

Do not modify the sofa frame, legs, or mechanisms, if any.
02.

Do not allow children to jump on the sofa or climb over the backrest and armrests.
04.

Do not exceed the recommended seating capacity or load limit of the sofa.

Storage and Environmental Care

01.

Store the sofa in a dry, clean, and well-ventilated area when not in use.
03.

Use a breathable fabric cover during long-term storage. Avoid airtight plastic covers that may trap moisture.
05.

Ensure the sofa is completely dry before covering or storing it.
02.

Avoid storing the sofa in damp rooms, outdoor areas, or locations exposed to rain, leaks, or high humidity.
04.

Do not stack heavy items on the sofa, cushions, armrests, or backrest.

Warranty and Customer Care Reminder

Damage caused by misuse, improper cleaning, exposure to heat, sunlight, moisture, overloading, unauthorized modification, or lack of reasonable maintenance may not be covered under warranty. Customers should follow the product label, assembly instructions, and any manufacturer-specific care guidance.

Quick Sofa Care Checklist

01.

Vacuum regularly.
03.

Keep away from sunlight, heat, flames, and moisture.
05.

Do not jump, stand, or overload the sofa.
07.

Use suitable cleaning products only after testing on a hidden area.
02.

Blot spills immediately.
04.

Fluff cushions.
06.

Check legs and fittings periodically.

8pm Sofa (Calm)

BP0001C

The 8pm sofa is built on one idea:

comfort over style. Its main investment is 7-inch high-density cushions for genuine comfort, paired with a spacious frame that seats 4+ people comfortably. Cushioned edges add child-safety for family use, and the design skips extra features to keep the price low.

Specification

Width	Depth	Height
2650mm	× 1065mm	× 710mm



Installation Guide



Scan Here
for video guide

01. Unpack Carefully

Cut open the packaging with scissors (avoid knives to prevent damage.)
02. Position the sofa pieces

Place both sides of the sofa where you want them.
03. Flip onto their backs

Turn both sofa sections so they rest on their backs.
04. Rotate the clips

Adjust the alligator clips so they face each other.
05. Flip upright again

Return both sofa pieces to their normal standing position.
06. Align the clips

Make sure the clips on both sides line up.
07. Connect the pieces

Push the sofa sections together until you hear multiple “clicks.” (You may need help from another person or a wall for support.)
08. Check the connection

If clips don’t lock, re-align and push again.
09. Assembly complete

Your sofa is ready to use!
10. To disconnect

Lift one side of the sofa slightly (front and back) to release the clips.

Direction of Use

01. Use the sofa for normal sitting, resting, and household use only.
02. Do not stand, jump, climb, or place excessive weight on the sofa, armrests, backrests, or cushions.
03. Place the sofa on a flat, stable, and dry surface to prevent rocking, uneven wear, or structural stress.
04. Keep the sofa away from direct sunlight, open flames, heaters, air-conditioner discharge, and excessive moisture.
05. Avoid placing sharp, hot, wet, or heavy objects directly on the sofa surface.
06. Lift the sofa when moving it. Do not drag it, as this may damage the sofa legs, frame, flooring, or upholstery.

Routine Cleaning and Maintenance

01. Vacuum the sofa regularly using a soft brush attachment to remove dust, crumbs, and loose dirt.
02. Blot spills immediately with a clean, dry, absorbent cloth. Do not rub, as rubbing may spread the stain or damage the upholstery.
03. For light cleaning, use a soft cloth slightly dampened with clean water, then allow the area to air dry completely.
04. Do not soak or saturate the sofa with water or cleaning solution.
05. Avoid bleach, strong solvents, abrasive cleaners, alcohol-based cleaners, and rough scrubbing tools unless specifically approved for the upholstery material.
06. Always test any cleaning product on a hidden area before applying it to visible surfaces.

Upholstery-Specific Care

Upholstery Type	Care Direction
01. Fabric sofa	Vacuum regularly and clean stains promptly by blotting. Keep away from prolonged direct sunlight to reduce fading. Allow fabric to dry fully before use.

Cushion, Frame, and Fitting Care

- 01. Fluff cushions regularly to help maintain shape and even wear.
- 02. Avoid sitting in the same position continuously for long periods, as this may cause uneven compression.
- 03. Do not pull or lift the sofa by the cushions, armrests, or upholstery fabric.
- 06. If the sofa produces unusual noise, becomes unstable, or shows structural damage, discontinue use until inspected or repaired.
- 05. Keep sofa legs dry and clean to prevent rust, swelling, corrosion, or floor staining, depending on the material.
- 04. Check legs, screws, brackets, and fittings periodically and tighten them when necessary.

Safety Precautions

- 01. Keep packaging materials, plastic bags, and small assembly parts away from children and pets.
- 02. Do not allow children to jump on the sofa or climb over the backrest and armrests.
- 03. Do not place the sofa near open flames, candles, hot appliances, or other fire hazards.
- 04. Do not exceed the recommended seating capacity or load limit of the sofa.
- 05. Do not modify the sofa frame, legs, or mechanisms, if any.

Storage and Environmental Care

- 01. Store the sofa in a dry, clean, and well-ventilated area when not in use.
- 02. Avoid storing the sofa in damp rooms, outdoor areas, or locations exposed to rain, leaks, or high humidity.
- 03. Use a breathable fabric cover during long-term storage. Avoid airtight plastic covers that may trap moisture.
- 04. Do not stack heavy items on the sofa, cushions, armrests, or backrest.
- 05. Ensure the sofa is completely dry before covering or storing it.

Warranty and Customer Care Reminder

Damage caused by misuse, improper cleaning, exposure to heat, sunlight, moisture, overloading, unauthorized modification, or lack of reasonable maintenance may not be covered under warranty. Customers should follow the product label, assembly instructions, and any manufacturer-specific care guidance.

Quick Sofa Care Checklist

- 01. Vacuum regularly.
- 02. Blot spills immediately.
- 03. Keep away from sunlight, heat, flames, and moisture.
- 04. Fluff cushions.
- 05. Do not jump, stand, or overload the sofa.
- 06. Check legs and fittings periodically.
- 07. Use suitable cleaning products only after testing on a hidden area.

11pm Bedframe

BPooo2K
BPooo2Q
BPooo2SS

King
Queen
Super Single

The 11pm bedframe is fully cushioned with soft, rounded edges for safer and more comfortable everyday use. Thoughtfully designed to be simple and timeless, they are made to stay with you for years.

Specification (King)			(Queen)			(Super Single)		
Width	Length	Height	Width	Length	Height	Width	Length	Height
2120mm	× 2250mm	× 300mm	1820mm	× 2250mm	× 450mm	1370mm	× 2250mm	× 300mm



Installation Guide



Scan Here
for video guide

01. Unpack Carefully
Cut open the packaging with scissors (avoid knives to prevent damage.)
03. Loosen the screws
Rotate the screws anticlockwise with the tool provided.
05. Level the bedframe
Push down on the side and front supports to make sure that they are level against the ground.
07. Install the middle supporting rod (Not relevant for Super Single)
 - Hook the middle supporting rod onto the front and back supports.
 - Make sure that the rod is straight and parallel to the side supports.
 - Re-position/Re-hook the rod if required, before screwing them tight.
09. Assembly complete
Your bedframe is ready for a mattress on top.
02. Position the bedframe pieces
 - Place the side supports parallel to each other.
 - Place the front and back supports in between the side supports and perpendicular to the side supports.
04. Connect the pieces
Hook the side supports onto the front and back supports.
06. Position the bedframe pieces
 - Fasten the screws tight by rotating clockwise with the tool provided.
 - It is advisable to fasten the screws gradually between the four corners to ensure that the bedframe remains level.
08. Place the bottom supporting boards
Fit the bottom supporting boards into place.
10. To disconnect
Repeat the steps above in reverse order.

Direction of Use

01. Use the bedframe only for normal sleeping, resting, and household bedroom use.
03. Use a mattress size suitable for the bedframe to ensure proper support and safe use.
05. Do not exceed the recommended load capacity of the bedframe, including mattress and users.
02. Place the bedframe on a flat, stable, and dry floor surface to prevent rocking, uneven pressure, or structural stress.
04. Do not stand, jump, or apply sudden impact on the bedframe, slats, side rails, headboard, or footboard.
06. Lift the bedframe when moving it. Do not drag it, as dragging may damage the frame, joints, legs, floor, or fittings.

Assembly, Support, and Fitting Care

01. Follow the assembly instructions carefully and ensure all parts are fitted in the correct position before use.
03. Ensure bed slats, boards, or support panels are correctly positioned and evenly spaced.
05. Avoid moving the bedframe while the mattress or heavy items are still on it, as this may strain the frame and fittings.
02. Check screws, bolts, brackets, legs, centre supports, and side rails periodically and tighten them when necessary.
04. Do not use the bedframe if any slat, support rail, leg, or joint is cracked, loose, bent, missing, or damaged.
06. If the bedframe produces unusual noise, feels unstable, or shifts during use, stop using it until inspected and adjusted.

Routine Cleaning and Maintenance

01.

Dust the bedframe regularly using a clean, soft, dry cloth or microfiber cloth.
02.

For light cleaning, wipe with a cloth slightly dampened with clean water, then dry immediately with a soft cloth.
03.

Vacuum around and under the bedframe regularly to remove dust and debris from joints, legs, and support areas.
04.

Wipe spills immediately and do not allow water or liquid to remain on the frame, slats, or fittings.
05.

Avoid abrasive cleaners, bleach, strong solvents, alcohol-based cleaners, ammonia, steel wool, and rough scrubbing pads.
06.

Always test any cleaning product on a hidden area before applying it to visible surfaces.

Material-Specific Care Instructions

Material	Care Direction
01. Wood, veneer, or engineered wood	Keep dry and away from direct sunlight, heat, and excessive humidity. Wipe spills immediately and avoid placing wet items against the frame.
02. Fabric	Vacuum gently using a soft brush attachment. Blot spills immediately and allow fabric to dry fully before use. Avoid heavy rubbing and excessive moisture.
03. Metal	Keep dry to reduce rust or corrosion. Wipe with a soft cloth and dry immediately. Check joints and fittings regularly, especially in humid environments.

Safety Precautions

01.

Keep packaging materials, plastic bags, small parts, and assembly hardware away from children and pets.
02.

Do not allow children to jump on, climb over, or play under the bedframe.
03.

Ensure the mattress is properly seated within the bedframe before use.
04.

Do not place hands, feet, or objects near moving parts, if any.
05.

Do not overload the bedframe.
06.

Do not modify, drill, cut, remove supports, or alter the bedframe unless recommended by the manufacturer.

Storage and Environmental Care

01.

Store dismantled bedframe parts in a clean, dry, and well-ventilated area.
02.

Keep parts away from damp walls, leaks, rain, direct sunlight, and high humidity.
03.

Store screws, bolts, brackets, and small fittings in a labelled bag to prevent loss.
04.

Protect visible surfaces from scratches or tears by wrapping or separating parts with soft material during storage or transport.
05.

Do not place heavy items on slats, panels, headboards, footboards, or upholstered sections during storage.

Warranty and Customer Care Reminder

Damage caused by misuse, overloading, improper assembly, dragging, impact, unsuitable cleaning products, exposure to moisture, unauthorized modification, or lack of reasonable maintenance may not be covered under warranty. Customers should follow the product label, assembly guide, and any manufacturer-specific care instructions.

Quick Bedframe Care Checklist

- 01. Use a suitable mattress size.
 - 02. Do not jump, stand, or overload the bedframe.
 - 03. Check screws, bolts, slats, legs, and supports periodically.
 - 04. Keep the bedframe dry and away from excessive heat, sunlight, and moisture.
 - 05. Lift the bedframe when moving it.
 - 06. Dust and clean regularly with suitable materials.
 - 07. Stop using the bedframe if it becomes unstable, cracked, loose, or damaged.
-

11pm Divan

BP0002DK

BP0002DQ

BP0002DSS

King

Queen

Super Single

The 11pm divan a non upholstered frame is fully Gently rounded, cushioned edges add an extra layer of safety and comfort to daily life. With a clean, timeless look, it's designed to stay with you for the long haul.

Specification (King)

Width

2120mm

Length

2050mm

Height

300mm

(Queen)

Width

1820mm

Length

2050mm

Height

450mm

(Super Single)

Width

1370mm

Length

2050mm

Height

300mm



Installation Guide



Scan Here
for video guide

01. Unpack Carefully
Cut open the packaging with scissors (avoid knives to prevent damage.)
03. Loosen the screws
Rotate the screws anticlockwise with the tool provided.
05. Level the divan
Push down on the side and front supports to make sure that they are level against the ground.
07. Install the middle supporting rod (Not relevant for Super Single)
 - Hook the middle supporting rod onto the front and back supports.
 - Make sure that the rod is straight and parallel to the side supports.
 - Re-position/Re-hook the rod if required, before screwing them tight.
09. Assembly complete
Your divan is ready for a mattress on top.
02. Position the divan pieces
 - Place the side supports parallel to each other.
 - Place the front and back supports in between the side supports and perpendicular to the side supports.
04. Connect the pieces
Hook the side supports onto the front and back supports.
06. Position the bedframe pieces
 - Fasten the screws tight by rotating clockwise with the tool provided.
 - It is advisable to fasten the screws gradually between the four corners to ensure that the bedframe remains level.
08. Place the bottom supporting boards
Fit the bottom supporting boards into place.
10. To disconnect
Repeat the steps above in reverse order.

Direction of Use

01. Use the bedframe only for normal sleeping, resting, and household bedroom use.
03. Use a mattress size suitable for the bedframe to ensure proper support and safe use.
05. Do not exceed the recommended load capacity of the bedframe, including mattress and users.
02. Place the bedframe on a flat, stable, and dry floor surface to prevent rocking, uneven pressure, or structural stress.
04. Do not stand, jump, or apply sudden impact on the bedframe, slats, side rails, headboard, or footboard.
06. Lift the bedframe when moving it. Do not drag it, as dragging may damage the frame, joints, legs, floor, or fittings.

Assembly, Support, and Fitting Care

01. Follow the assembly instructions carefully and ensure all parts are fitted in the correct position before use.
03. Ensure bed slats, boards, or support panels are correctly positioned and evenly spaced.
05. Avoid moving the bedframe while the mattress or heavy items are still on it, as this may strain the frame and fittings.
02. Check screws, bolts, brackets, legs, centre supports, and side rails periodically and tighten them when necessary.
04. Do not use the bedframe if any slat, support rail, leg, or joint is cracked, loose, bent, missing, or damaged.
06. If the bedframe produces unusual noise, feels unstable, or shifts during use, stop using it until inspected and adjusted.

Routine Cleaning and Maintenance

01. Dust the bedframe regularly using a clean, soft, dry cloth or microfiber cloth.

03. Vacuum around and under the bedframe regularly to remove dust and debris from joints, legs, and support areas.

05. Avoid abrasive cleaners, bleach, strong solvents, alcohol-based cleaners, ammonia, steel wool, and rough scrubbing pads.
02. For light cleaning, wipe with a cloth slightly dampened with clean water, then dry immediately with a soft cloth.

04. Wipe spills immediately and do not allow water or liquid to remain on the frame, slats, or fittings.

06. Always test any cleaning product on a hidden area before applying it to visible surfaces.

Material-Specific Care Instructions

Material	Care Direction
01. Wood, veneer, or engineered wood	Keep dry and away from direct sunlight, heat, and excessive humidity. Wipe spills immediately and avoid placing wet items against the frame.
02. Fabric	Vacuum gently using a soft brush attachment. Blot spills immediately and allow fabric to dry fully before use. Avoid heavy rubbing and excessive moisture.
03. Metal	Keep dry to reduce rust or corrosion. Wipe with a soft cloth and dry immediately. Check joints and fittings regularly, especially in humid environments.

Safety Precautions

01. Keep packaging materials, plastic bags, small parts, and assembly hardware away from children and pets.

03. Ensure the mattress is properly seated within the bedframe before use.

05. Do not overload the bedframe.
02. Do not allow children to jump on, climb over, or play under the bedframe.

04. Do not place hands, feet, or objects near moving parts, if any.

06. Do not modify, drill, cut, remove supports, or alter the bedframe unless recommended by the manufacturer.

Storage and Environmental Care

01. Store dismantled bedframe parts in a clean, dry, and well-ventilated area.

03. Store screws, bolts, brackets, and small fittings in a labelled bag to prevent loss.

05. Do not place heavy items on slats, panels, headboards, footboards, or upholstered sections during storage.
02. Keep parts away from damp walls, leaks, rain, direct sunlight, and high humidity.

04. Protect visible surfaces from scratches or tears by wrapping or separating parts with soft material during storage or transport.

Warranty and Customer Care Reminder

Damage caused by misuse, overloading, improper assembly, dragging, impact, unsuitable cleaning products, exposure to moisture, unauthorized modification, or lack of reasonable maintenance may not be covered under warranty. Customers should follow the product label, assembly guide, and any manufacturer-specific care instructions.

Quick Bedframe Care Checklist

- 01. Use a suitable mattress size.
 - 02. Do not jump, stand, or overload the bedframe.
 - 03. Check screws, bolts, slats, legs, and supports periodically.
 - 04. Keep the bedframe dry and away from excessive heat, sunlight, and moisture.
 - 05. Lift the bedframe when moving it.
 - 06. Dust and clean regularly with suitable materials.
 - 07. Stop using the bedframe if it becomes unstable, cracked, loose, or damaged.
-

11pm Mattress

BPooo3K
BPooo3Q
BPooo3SS

King
Queen
Super Single

11pm Mattress is designed to provide balanced softness with firm support for comfortable, restful sleep. At 300 mm thick, it offers premium comfort at an affordable price.

Specification (King)			(Queen)			(Super Single)		
Width	Length	Height	Width	Length	Height	Width	Length	Height
1820mm	× 1900mm	× 300mm	1520mm	× 1900mm	× 300mm	1070mm	× 1900mm	× 300mm



Materials By Layers

01. Cooling Fabric
02. 1 cm Latex
03. 2 cm High-Density Foam
04. 2 cm Soft Foam
05. 3 cm High-Density Foam
06. 1 cm 3-Zone Pocket Spring (2.0/2.2 mm)
07. 2 Rows Edge Support
08. TC Fabric
09. 0.5 cm High-Density Foam

Installation Guide

01. Unpack Carefully
Cut open the packaging box on one side with scissors (avoid knives to prevent damage).
02. Remove Box
Slide the mattress out of the box by lifting the opposite side.
03. Unroll mattress
Unwind the mattress by pulling the plastic sheet towards yourself.
04. Position mattress
 - Place the mattress upright on the bedframe.
 - Take note on the orientation of the mattress and rotate if necessary. The side with spring coils is the bottom of the mattress.
05. Level the bedframe
Push down on the side and front supports to make sure that they are level against the ground.
06. Remove packaging
Take off the plastic packaging.
07. Allow time for mattress to expand
Leave the mattress for 48 hours to fully expand before using it.
08. Unbox complete
Your mattress is ready for you to enjoy!



Scan Here
for video guide

Direction of Use

01. Use the mattress only for normal sleeping, resting, and household bedroom use.
02. Place the mattress on a suitable bedframe, platform, or support base that provides even support across the mattress.
03. Ensure the mattress size matches the bedframe to prevent gaps, bending, sagging, or unsafe use.
04. Do not stand, jump, fold, bend, or place heavy concentrated weight on the mattress.
05. Use a mattress protector or fitted sheet to help protect the surface from stains, sweat, dust, and daily wear.
06. Allow the mattress to breathe by keeping the sleeping area well ventilated and avoiding prolonged moisture exposure.

Rotation, Support, and Shape Care

01. Rotate the mattress from head to foot regularly.
02. Do not flip a one-sided mattress unless the product is specifically designed for two-sided use.
03. Use proper support such as firm slats, a solid platform, or a compatible bed base to reduce sagging.
04. Check the bed base, slats, and support structure periodically to ensure they remain flat, stable, and correctly positioned.
05. Avoid sitting on the same edge of the mattress repeatedly for long periods, as this may cause uneven compression.
06. Minor body impressions may occur with normal use.

Routine Cleaning and Maintenance

01.

Vacuum the mattress surface regularly using a clean upholstery attachment to remove dust and loose particles.
03.

For light spot cleaning, use only a small amount of mild cleaner suitable for mattress fabric, then blot and allow the area to dry completely.
05.

Do not use bleach, strong solvents, harsh chemicals, abrasive cleaners, or excessive water on the mattress.
02.

Blot spills immediately with a clean, dry, absorbent cloth. Do not rub or scrub the affected area.
04.

Do not soak, saturate, steam-clean, pressure-wash, or machine-wash the mattress unless specifically permitted by the manufacturer.
06.

Ensure the mattress is completely dry before covering it with sheets, mattress protectors, or bedding.

Safety Precautions

01.

Keep plastic packaging, wrapping, and small accessories away from children and pets.
03.

Do not smoke on or near the mattress.
05.

Ensure the mattress fits securely on the bedframe to reduce gaps and movement during use.
02.

Do not use the mattress near open flames, candles, heaters, or other heat sources.
04.

Do not allow children to jump on the mattress, as this may damage the mattress and increase the risk of injury.
06.

Discontinue use if the mattress is torn, contaminated, wet, mouldy, infested, or structurally damaged.

Storage and Transport Care

01.

Store the mattress flat in a clean, dry, and well-ventilated area whenever possible.
03.

Do not place heavy items on top of the mattress during storage, as this may cause compression or deformation.
05.

Carry the mattress carefully using two or more people when needed. Do not drag the mattress across rough surfaces.
02.

Avoid storing the mattress in damp rooms, outdoor areas, or locations exposed to leaks, rain, direct sunlight, or high humidity.
04.

Use a breathable protective cover for storage. Avoid airtight plastic covers for long periods, as they may trap moisture.
06.

Avoid folding or rolling the mattress

Warranty and Customer Care Reminder

Damage caused by misuse, unsuitable bed support, bending, folding, dragging, jumping, liquid exposure, stains, mould, infestation, heat exposure, improper cleaning, or lack of reasonable maintenance may not be covered under warranty. Customers should follow the product label, care tag, delivery instructions, and any manufacturer-specific care guidance supplied with the mattress.

Quick Mattress Care Checklist

01.

Use a suitable bedframe or support base.
03.

Rotate regularly unless instructed otherwise.
05.

Keep the mattress dry, clean, and well ventilated.
07.

Allow the mattress to dry completely before covering or using it again.
02.

Use a mattress protector or fitted sheet.
04.

Do not jump, stand, fold, bend, or drag the mattress.
06.

Vacuum regularly and blot spills immediately.

Kitchen Piano

BP0004

Kitchen Piano is a multifunctional sink with buttons inspired by a piano. Its soothing water flow and multiple washing angles help reduce splashing, making everyday dishwashing cleaner and more enjoyable.

Specification

Width	Length	Height
750mm	× 450mm	× 250mm



Installation Guide



Scan Here
for video guide

01. Prepare the countertop

 - Verify the sink dimensions against the countertop opening.
 - Use the dimensions (710 mm x 420 mm) provided to mark the cutout.
 - Cut the opening with appropriate tools according to the countertop material.
 - Smooth the edges with sandpaper.
03. Separate accessories

Detach all accessories from the sink.
05. Prepare the countertop

 - Align the sink rim with the countertop edges.
 - Press down firmly to seat the sink into the sealant.
 - Wipe away excess caulk immediately.
07. Connect plumbing

 - Connect water supply hoses to faucet.
 - Attach waste water trap and drain assembly.
 - Use plumber's tape on threaded joints to prevent leaks.
 - Test for leaks by running water
02. Unpack carefully

Cut open the packaging box on the top with scissors (avoid knives to prevent damage).
04. Apply sealant

 - Run a bead of silicone caulk around the underside of the sink rim.
 - Ensure even coverage to prevent leaks.
06. Install faucet and accessories

 - Install accessories and buttons deck onto the sink.
 - Attach the faucet to the sink deck holes.
 - Attach other accessories such as soap dispenser and cup washer.
 - Tighten mounting nuts securely.
08. Final checks

 - Inspect sealant bead for gaps
 - Confirm faucet and accessories operate correctly.

Direction of Use

01. Use the kitchen sink only for normal household washing, rinsing, draining, and food preparation activities.
03. Do not stand, sit, step, or place excessive weight on the sink, drainboard, faucet area, or accessories.
05. Use the supplied accessories only for their intended purpose, such as washing, rinsing, draining, cutting support, or storage as applicable.
02. Ensure the sink is properly installed, supported, sealed, and connected to the drainage system before use.
04. Avoid dropping heavy pots, pans, knives, tools, or hard objects into the sink, as impact may dent, chip, crack, or scratch the surface.
06. Do not pour boiling oil, paint, cement, strong chemicals, or corrosive liquids into the sink or drain.

Routine Cleaning and Maintenance

01. Rinse the sink with clean water after daily use to remove soap, food residue, minerals, and cleaning product residue.
03. Wipe the sink dry after cleaning to reduce water spots, mineral marks, and surface staining.
05. Do not use steel wool, metal scouring pads, abrasive powders, bleach, strong acids, strong alkalis, or harsh solvents unless specifically approved for the sink material.
02. Clean with a soft sponge or cloth using mild dishwashing liquid and clean water, then rinse thoroughly.
04. Remove food scraps from the sink basket, strainer, and drain area regularly to prevent blockage and odour.
06. Always test any cleaning product on a hidden or less visible area before applying it to the whole sink surface.

Material and Accessory-Specific Care

Component	Care Direction
01. Stainless steel sink	Clean along the grain where visible. Rinse and dry after use to reduce water marks. Avoid prolonged contact with salt, acidic food residue, bleach, or metal objects that may cause staining or rust marks.
02. Drain basket, strainer, and waste fitting	Empty food residue regularly. Rinse and clean to prevent odour, blockage, and build-up. Ensure fittings are correctly seated after cleaning.
03. Cutting board accessory	Use only as intended and clean after each use. Do not soak for long periods. Dry completely before storage to reduce warping, odour, or mould growth.
04. Colander, tray, rack, basket, or drainer	Rinse after use and dry before storing. Do not overload or use as a step, seat, or support for heavy appliances.
05. Soap dispenser, cup washer, or faucet accessory	Use compatible liquid only and avoid thick, corrosive, or abrasive solutions. Wipe surfaces regularly and check for leaks or loose fittings.

Drainage, Hygiene, and Odour Control

01. Keep the drain area clear of food waste, grease, hair, labels, plastic pieces, and other debris.	02. Do not pour cooking oil, grease, or fat directly into the sink drain, as these may harden and cause blockage.
03. Flush the drain regularly with clean water after use, especially after washing oily or heavily soiled items.	04. Clean removable strainers, baskets, racks, and trays regularly to prevent bacteria build-up and unpleasant odours.
05. If drainage slows, stop using the sink until the blockage is checked and cleared using a suitable method.	06. Do not force sharp tools, rods, or unsuitable chemicals into the drain, as this may damage pipes, seals, or fittings.

Safety Precautions

01. Keep plastic packaging, wrapping, and small accessories away from children and pets.	02. Use caution when handling sharp kitchen tools, knives, blades, or broken glass around
03. Do not allow children to climb, sit, or play on the sink, countertop, faucet, or accessories.	04. Use heat-resistant protection when placing hot cookware near or on compatible sink accessories, and avoid exposing non-heat-resistant accessories to high heat.
05. Check underneath the sink periodically for leaks, loose pipes, loose clips, damp cabinets, or water marks.	06. Discontinue use and arrange inspection if the sink becomes loose, cracked, leaking, blocked, unstable, or visibly damaged.

Storage and Care for Removable Accessories

01.

Keep packaging materials, plastic bags, clips, small parts, and installation accessories away from children and pets.
03.

Do not allow children to climb, sit, or play on the sink, countertop, faucet, or accessories.
05.

Check underneath the sink periodically for leaks, loose pipes, loose clips, damp cabinets, or water marks.
02.

Use caution when handling sharp kitchen tools, knives, blades, or broken glass around the sink area.
04.

Use heat-resistant protection when placing hot cookware near or on compatible sink accessories, and avoid exposing non-heat-resistant accessories to high heat.
06.

Discontinue use and arrange inspection if the sink becomes loose, cracked, leaking, blocked, unstable, or visibly damaged.

Warranty and Customer Care Reminder

Damage caused by improper installation, misuse, impact, overloading, harsh chemicals, abrasive cleaning tools, blocked drainage, corrosion from unsuitable substances, unauthorized modification, or lack of reasonable maintenance may not be covered under warranty. Customers should follow the product label, installation guide, accessory instructions, and any manufacturer-specific care guidance.

Quick Kitchen Sink Care Checklist

01.

Rinse and wipe dry after daily use.
03.

Remove food waste from the basket, strainer, and drain area regularly.
05.

Avoid steel wool, abrasive pads, bleach, strong acids, and harsh solvents.
07.

Check for leaks, loose fittings, blockage, or damage periodically.
02.

Use mild dishwashing liquid and a soft sponge or cloth.
04.

Do not pour oil, grease, strong chemicals, or corrosive liquids into the sink.
06.

Clean and dry accessories before storage.

First Step SPC Flooring

BP0005

SPC flooring is widely used around the world for its durability, water resistance, and ease of repair or replacement. Bersama Project's First Step SPC features a timeless wood-inspired finish that brings warmth and lasting style to any home.

Specification

Width Length Height
1220mm × 184mm × 4mm (26.94sqft)

12pcs x 1.9kg



Installation Guide

- o1. Check the product and site condition
 - Inspect all cartons and planks before installation. Do not install damaged, warped, chipped, or visibly defective planks.
 - Confirm the colour, design, batch, and quantity before starting work.
 - Ensure the room is enclosed, dry, clean, and suitable for indoor flooring installation.
- o3. Acclimate the flooring
 - Ensure the subfloor is clean, dry, level, stable, and free from dust, grease, wax, adhesive residue, nails, debris, and loose particles.
 - Repair cracks, holes, high spots, low spots, or uneven areas using suitable patching or levelling material.
 - Concrete subfloors must be properly cured and dry before installation.
 - Do not install over soft, unstable, damp, mouldy, or uneven surfaces.
- o5. Install the first row
 - Start from a straight wall and use spacers to maintain the required expansion gap around the perimeter.
 - Place the tongue or groove side according to the locking system instructions.
 - Keep the first row straight, as it will guide the rest of the installation.
- o7. Cut and fit edge planks
 - Measure carefully before cutting the last plank in each row and the final row.
 - Wear suitable protective equipment when cutting, including gloves, eye protection, and a mask.
 - Leave expansion gaps at walls, door frames, pipes, columns, cabinets, and other fixed structures.
- o9. Final checks
 - Remove spacers and check that all planks are locked properly with no visible gaps, lifted edges, or loose sections.
 - Clean installation dust with a soft broom, vacuum with hard-floor setting, or dry microfiber mop.
 - Do not wash heavily, steam-clean, or expose the floor to standing water immediately after installation.
- o2. Acclimate the flooring
 - Store SPC flooring flat in the installation area for 24–48 hours before installation.
 - Keep cartons flat and unopened where possible to protect the locking edges.
 - Maintain stable room conditions before, during, and after installation.
- o4. Plan the layout
 - Measure the room and plan the plank direction before installation.
 - Mix planks from several cartons to achieve a natural colour and pattern variation.
 - Stagger short-end joints between rows to improve appearance and stability.
 - Check door clearance, wall edges, and fixed structures before laying the first row.
- o6. Connect the planks
 - Fit the short and long edges together using the recommended click-lock method.
 - Do not force the locking system if the plank is not aligned; lift and reposition before locking.
 - Use suitable installation tools where required and avoid damaging the plank edges.
- o8. Install trims and accessories
 - Install skirting, T-moulding, L-moulding, transition strips, or edge trims as required.
 - Do not fasten trims through floating floor planks in a way that prevents natural floor movement.
 - Ensure accessories are aligned and firmly fixed according to the manufacturer's instructions.



Scan Here
for video guide

Direction of Use

- 01. Use SPC flooring only for suitable indoor residential or light commercial applications.
- 03. Keep the floor free from sand, stones, grit, sharp objects, and hard debris that may scratch the surface.
- 05. Use felt pads under furniture legs and suitable protective mats under rolling chairs, heavy appliances, and frequently moved furniture.
- 07. Use curtains, blinds, or UV protection in areas exposed to strong direct sunlight to reduce fading, discoloration, or heat-related movement.
- 02. Do not install or use SPC flooring outdoors, in open balconies, saunas, wet rooms with standing water, or areas exposed to continuous water flow.
- 04. Lift furniture and appliances when moving them. Do not drag heavy items across the floor.
- 06. Avoid placing hot items, burning materials, cigarettes, or open flames directly on the floor.

Initial Use and Early Care

- 01. Allow the flooring to settle after installation before heavy use, heavy cleaning, or moving large furniture back into place.
- 03. Maintain good ventilation during and after installation, especially when adhesives, sealants, or trims are used.
- 05. Place entrance mats at doorways immediately after installation to reduce grit and dirt being carried onto the floor.
- 02. For adhesive installation, allow the adhesive to cure fully according to the adhesive manufacturer's instructions before wet cleaning or heavy traffic.
- 04. Check the floor after installation for raised edges, gaps, damaged planks, or areas that do not lock properly.

Routine Cleaning and Maintenance

- 01. Sweep, dust-mop, or vacuum regularly using a soft broom, microfiber mop, or vacuum with a hard-floor setting.
- 03. Mop with a damp, well-wrung microfiber mop and a mild pH-neutral cleaner suitable for vinyl or SPC flooring.
- 05. For sticky marks or scuffs, use a soft cloth and manufacturer-approved cleaner. Always test cleaning products on a hidden area first.
- 07. Do not pour water directly onto the floor or allow water to pool along joints, skirting, transitions, or wall edges.
- 02. Do not use vacuums with rotating beater bars or stiff brushes that may scratch the floor surface.
- 04. Wipe spills immediately with a soft absorbent cloth to prevent staining, slipping, or moisture entering joints.
- 06. Do not use steam cleaners, excessive water, wax, polish, oil soap, abrasive powders, steel wool, bleach, ammonia, strong acids, strong alkalis, or harsh solvents.

Area-Specific Care Instructions

Area or Condition	Care Direction
01. Kitchens and dining areas	Wipe food, oil, and drink spills promptly. Use mats near sinks, stoves, and preparation areas to reduce water, grease, and grit exposure.
02. Laundry areas, and wet prone zones	Maintain ventilation, wipe splashes and condensation promptly, and do not allow standing water to remain on the floor or around edges.
03. Entrances and corridors	Use non-staining entrance mats and clean frequently to remove sand, grit, and dirt that may cause scratches or dulling.
04. Living rooms and bedrooms	Use felt pads under furniture legs and lift furniture when rearranging. Avoid dragging beds, cabinets, tables, or chairs across the floor.
05. Office or commercial use	Use chair mats under rolling chairs and protective boards when moving heavy equipment. Increase cleaning frequency in high-traffic areas.

Repair and Replacement Care

01. Keep spare planks from the same batch where possible for future repairs and colour matching.	02. For light scuffs or minor marks, clean gently with a soft cloth and manufacturer-approved cleaner.
03. For small scratches or chips, use only manufacturer-approved repair kits, touch-up solutions, or fillers suitable for SPC flooring.	04. Replace deeply scratched, cracked, swollen, lifted, or broken planks promptly to prevent further damage or unsafe walking conditions.
05. Use felt pads under furniture legs and suitable protective mats under rolling chairs, heavy appliances, and frequently moved furniture.	06. Before repair or replacement, identify and correct the cause of damage, such as moisture, uneven subfloor, dragging furniture, impact, or unsuitable cleaning products.

Repair Guide

01. Identify damaged plank • Confirm which plank needs replacement. • Inspect for cracks, chips or water damage. • Mark the damaged plank with tape.	02. Prepare the work area • Remove furniture and rugs. • Clean dust and debris around the damaged plank. • Wear gloves and safety glasses.
03. Cut and remove plank • Carefully cut the damaged plank to remove it without disturbing others. • Use a circular saw or blade set to plank thickness of ca. 4mm. • Cut two parallel lines lengthwise inside the plank. • Pry out the centre piece, then remove remaining edges with a chisel.	04. Clean floor • Ensure the exposed floor is ready for the new plank. • Remove adhesive residue or debris. • Check for moisture or unevenness. • Vacuum the area thoroughly.

- o5. Trim replacement plank

 - Modify the new plank so it can fit into the gap
 - Cut off the tongue and groove edges.
 - Dry fit without any adhesive to confirm alignment.
 - Ensure colour and pattern match existing floor.
- o6. Install new plank

 - Secure the replacement plank in place.
 - Apply flooring adhesive to the floor
 - Place plank into the gap and press firmly.
 - Use a weighted object to hold it flat during curing.
- o7. Finish and inspect

 - Check the repair for stability and appearance.
 - Wipe away excess adhesive
 - Ensure the plank is level with surrounding floor.
 - Allow 24 hours before heavy use.

Safety Precautions

- o1. Read and follow the product label, installation guide, technical data sheet, and safety instructions before installation or use.

o2. Keep planks, packaging materials, cutting tools, adhesives, spacers, trims, and small parts away from children and pets.
- o3. Wear suitable protective equipment when cutting or installing planks, including gloves, eye protection, and a mask.

o4. Use cutting tools carefully and cut planks in a safe, stable, and well-ventilated area.
- o5. Ensure good ventilation when using adhesives, sealants, or cleaning products.

o6. Do not use damaged flooring areas that are lifted, loose, slippery, cracked, or unstable until repaired.

Storage, Handling, and Disposal

- o1. Store SPC flooring flat in its original packaging on a clean, dry, level, and supported surface.

o2. Keep flooring in a cool, dry, shaded, and well-ventilated area away from direct sunlight, moisture, leaks, and extreme temperatures.
- o3. Do not store cartons upright, on their sides, or in areas where locking edges may be damaged.

o4. Handle planks carefully to avoid chipping corners, breaking locking profiles, or scratching the surface.
- o5. Dispose of offcuts, damaged planks, packaging, adhesives, and installation waste according to local regulations.

o6. Do not burn SPC flooring or dispose of installation waste in an unsafe manner.

Warranty and Customer Care Reminder

SPC flooring performance may be affected by improper installation, unsuitable subfloor conditions, excessive moisture, standing water, poor ventilation, direct heat, heavy impact, dragging furniture, harsh cleaning products, abrasive tools, unauthorized modification, or lack of reasonable maintenance. Damage or failure caused by these conditions may not be covered under warranty. Customers should follow the product label, installation guide, technical data sheet, safety information, and any manufacturer-specific care guidance supplied with the flooring.

Quick SPC Flooring Care Checklist

- 01. Inspect planks before installation.
- 02. Acclimate and store planks flat before installation.
- 03. Prepare a clean, dry, level, and stable subfloor.
- 04. Maintain correct expansion gaps around walls and fixed structures.
- 05. Sweep or vacuum regularly using soft hard-floor tools.
- 06. Damp mop only with a mild pH-neutral cleaner.
- 07. Wipe spills immediately and avoid standing water.
- 08. Do not use steam cleaners, wax, polish, abrasive pads, bleach, ammonia, or harsh solvents.
- 09. Use entrance mats, felt pads, and chair mats to protect the floor.
- 10. Repair or replace damaged planks promptly and keep spare planks for future matching.

First Step T Moulding

BP0005A

Specification

Width Length Height
2400mm × 45mm × 6mm

25 pcs/ ctn

Pending
image



Installation Guide

- o1. Check the product and site condition
 - Inspect all cartons and planks before installation. Do not install damaged, warped, chipped, or visibly defective planks.
 - Confirm the colour, design, batch, and quantity before starting work.
 - Ensure the room is enclosed, dry, clean, and suitable for indoor flooring installation.
- o3. Acclimate the flooring
 - Ensure the subfloor is clean, dry, level, stable, and free from dust, grease, wax, adhesive residue, nails, debris, and loose particles.
 - Repair cracks, holes, high spots, low spots, or uneven areas using suitable patching or levelling material.
 - Concrete subfloors must be properly cured and dry before installation.
 - Do not install over soft, unstable, damp, mouldy, or uneven surfaces.
- o5. Install the first row
 - Start from a straight wall and use spacers to maintain the required expansion gap around the perimeter.
 - Place the tongue or groove side according to the locking system instructions.
 - Keep the first row straight, as it will guide the rest of the installation.
- o7. Cut and fit edge planks
 - Measure carefully before cutting the last plank in each row and the final row.
 - Wear suitable protective equipment when cutting, including gloves, eye protection, and a mask.
 - Leave expansion gaps at walls, door frames, pipes, columns, cabinets, and other fixed structures.
- o9. Final checks
 - Remove spacers and check that all planks are locked properly with no visible gaps, lifted edges, or loose sections.
 - Clean installation dust with a soft broom, vacuum with hard-floor setting, or dry microfiber mop.
 - Do not wash heavily, steam-clean, or expose the floor to standing water immediately after installation.
- o2. Acclimate the flooring
 - Store SPC flooring flat in the installation area for 24–48 hours before installation.
 - Keep cartons flat and unopened where possible to protect the locking edges.
 - Maintain stable room conditions before, during, and after installation.
- o4. Plan the layout
 - Measure the room and plan the plank direction before installation.
 - Mix planks from several cartons to achieve a natural colour and pattern variation.
 - Stagger short-end joints between rows to improve appearance and stability.
 - Check door clearance, wall edges, and fixed structures before laying the first row.
- o6. Connect the planks
 - Fit the short and long edges together using the recommended click-lock method.
 - Do not force the locking system if the plank is not aligned; lift and reposition before locking.
 - Use suitable installation tools where required and avoid damaging the plank edges.
- o8. Install trims and accessories
 - Install skirting, T-moulding, L-moulding, transition strips, or edge trims as required.
 - Do not fasten trims through floating floor planks in a way that prevents natural floor movement.
 - Ensure accessories are aligned and firmly fixed according to the manufacturer's instructions.



Scan Here
for video guide

Direction of Use

- 01. Use SPC flooring only for suitable indoor residential or light commercial applications.
- 02. Do not install or use SPC flooring outdoors, in open balconies, saunas, wet rooms with standing water, or areas exposed to continuous water flow.
- 03. Keep the floor free from sand, stones, grit, sharp objects, and hard debris that may scratch the surface.
- 04. Lift furniture and appliances when moving them. Do not drag heavy items across the floor.
- 05. Use felt pads under furniture legs and suitable protective mats under rolling chairs, heavy appliances, and frequently moved furniture.
- 06. Avoid placing hot items, burning materials, cigarettes, or open flames directly on the floor.
- 07. Use curtains, blinds, or UV protection in areas exposed to strong direct sunlight to reduce fading, discoloration, or heat-related movement.

Initial Use and Early Care

- 01. Allow the flooring to settle after installation before heavy use, heavy cleaning, or moving large furniture back into place.
- 02. For adhesive installation, allow the adhesive to cure fully according to the adhesive manufacturer's instructions before wet cleaning or heavy traffic.
- 03. Maintain good ventilation during and after installation, especially when adhesives, sealants, or trims are used.
- 04. Check the floor after installation for raised edges, gaps, damaged planks, or areas that do not lock properly.
- 05. Place entrance mats at doorways immediately after installation to reduce grit and dirt being carried onto the floor.

Routine Cleaning and Maintenance

- 01. Sweep, dust-mop, or vacuum regularly using a soft broom, microfiber mop, or vacuum with a hard-floor setting.
- 02. Do not use vacuums with rotating beater bars or stiff brushes that may scratch the floor surface.
- 03. Mop with a damp, well-wrung microfiber mop and a mild pH-neutral cleaner suitable for vinyl or SPC flooring.
- 04. Wipe spills immediately with a soft absorbent cloth to prevent staining, slipping, or moisture entering joints.
- 05. For sticky marks or scuffs, use a soft cloth and manufacturer-approved cleaner. Always test cleaning products on a hidden area first.
- 06. Do not use steam cleaners, excessive water, wax, polish, oil soap, abrasive powders, steel wool, bleach, ammonia, strong acids, strong alkalis, or harsh solvents.
- 07. Do not pour water directly onto the floor or allow water to pool along joints, skirting, transitions, or wall edges.

Area-Specific Care Instructions

Area or Condition	Care Direction
01. Kitchens and dining areas	Wipe food, oil, and drink spills promptly. Use mats near sinks, stoves, and preparation areas to reduce water, grease, and grit exposure.
02. Laundry areas, and wet prone zones	Maintain ventilation, wipe splashes and condensation promptly, and do not allow standing water to remain on the floor or around edges.
03. Entrances and corridors	Use non-staining entrance mats and clean frequently to remove sand, grit, and dirt that may cause scratches or dulling.
04. Living rooms and bedrooms	Use felt pads under furniture legs and lift furniture when rearranging. Avoid dragging beds, cabinets, tables, or chairs across the floor.
05. Office or commercial use	Use chair mats under rolling chairs and protective boards when moving heavy equipment. Increase cleaning frequency in high-traffic areas.

Repair and Replacement Care

01. Keep spare planks from the same batch where possible for future repairs and colour matching.	02. For light scuffs or minor marks, clean gently with a soft cloth and manufacturer-approved cleaner.
03. For small scratches or chips, use only manufacturer-approved repair kits, touch-up solutions, or fillers suitable for SPC flooring.	04. Replace deeply scratched, cracked, swollen, lifted, or broken planks promptly to prevent further damage or unsafe walking conditions.
05. Use felt pads under furniture legs and suitable protective mats under rolling chairs, heavy appliances, and frequently moved furniture.	06. Before repair or replacement, identify and correct the cause of damage, such as moisture, uneven subfloor, dragging furniture, impact, or unsuitable cleaning products.

Repair Guide

01. Identify damaged plank • Confirm which plank needs replacement. • Inspect for cracks, chips or water damage. • Mark the damaged plank with tape.	02. Prepare the work area • Remove furniture and rugs. • Clean dust and debris around the damaged plank. • Wear gloves and safety glasses.
03. Cut and remove plank • Carefully cut the damaged plank to remove it without disturbing others. • Use a circular saw or blade set to plank thickness of ca. 4mm. • Cut two parallel lines lengthwise inside the plank. • Pry out the centre piece, then remove remaining edges with a chisel.	04. Clean floor • Ensure the exposed floor is ready for the new plank. • Remove adhesive residue or debris. • Check for moisture or unevenness. • Vacuum the area thoroughly.

- o5. Trim replacement plank

 - Modify the new plank so it can fit into the gap
 - Cut off the tongue and groove edges.
 - Dry fit without any adhesive to confirm alignment.
 - Ensure colour and pattern match existing floor.
- o6. Install new plank

 - Secure the replacement plank in place.
 - Apply flooring adhesive to the floor
 - Place plank into the gap and press firmly.
 - Use a weighted object to hold it flat during curing.
- o7. Finish and inspect

 - Check the repair for stability and appearance.
 - Wipe away excess adhesive
 - Ensure the plank is level with surrounding floor.
 - Allow 24 hours before heavy use.

Safety Precautions

- o1. Read and follow the product label, installation guide, technical data sheet, and safety instructions before installation or use.

o2. Keep planks, packaging materials, cutting tools, adhesives, spacers, trims, and small parts away from children and pets.
- o3. Wear suitable protective equipment when cutting or installing planks, including gloves, eye protection, and a mask.

o4. Use cutting tools carefully and cut planks in a safe, stable, and well-ventilated area.
- o5. Ensure good ventilation when using adhesives, sealants, or cleaning products.

o6. Do not use damaged flooring areas that are lifted, loose, slippery, cracked, or unstable until repaired.

Storage, Handling, and Disposal

- o1. Store SPC flooring flat in its original packaging on a clean, dry, level, and supported surface.

o2. Keep flooring in a cool, dry, shaded, and well-ventilated area away from direct sunlight, moisture, leaks, and extreme temperatures.
- o3. Do not store cartons upright, on their sides, or in areas where locking edges may be damaged.

o4. Handle planks carefully to avoid chipping corners, breaking locking profiles, or scratching the surface.
- o5. Dispose of offcuts, damaged planks, packaging, adhesives, and installation waste according to local regulations.

o6. Do not burn SPC flooring or dispose of installation waste in an unsafe manner.

Warranty and Customer Care Reminder

SPC flooring performance may be affected by improper installation, unsuitable subfloor conditions, excessive moisture, standing water, poor ventilation, direct heat, heavy impact, dragging furniture, harsh cleaning products, abrasive tools, unauthorized modification, or lack of reasonable maintenance. Damage or failure caused by these conditions may not be covered under warranty. Customers should follow the product label, installation guide, technical data sheet, safety information, and any manufacturer-specific care guidance supplied with the flooring.

Quick SPC T Moulding Care Checklist

01. Inspect planks before installation.

03. Prepare a clean, dry, level, and stable subfloor.

05. Sweep or vacuum regularly using soft hard-floor tools.

07. Wipe spills immediately and avoid standing water.

09. Use entrance mats, felt pads, and chair mats to protect the floor.
02. Acclimate and store planks flat before installation.

04. Maintain correct expansion gaps around walls and fixed structures.

06. Damp mop only with a mild pH-neutral cleaner.

08. Do not use steam cleaners, wax, polish, abrasive pads, bleach, ammonia, or harsh solvents.

10. Repair or replace damaged planks promptly and keep spare planks for future matching.

First Step L Moulding

BP0005B

Specification

Width Length Height
2400mm × 30mm × 30mm

100 pcs/ ctn

Pending
image



Installation Guide

- o1. Check the product and site condition
 - Inspect all cartons and planks before installation. Do not install damaged, warped, chipped, or visibly defective planks.
 - Confirm the colour, design, batch, and quantity before starting work.
 - Ensure the room is enclosed, dry, clean, and suitable for indoor flooring installation.
- o3. Acclimate the flooring
 - Ensure the subfloor is clean, dry, level, stable, and free from dust, grease, wax, adhesive residue, nails, debris, and loose particles.
 - Repair cracks, holes, high spots, low spots, or uneven areas using suitable patching or levelling material.
 - Concrete subfloors must be properly cured and dry before installation.
 - Do not install over soft, unstable, damp, mouldy, or uneven surfaces.
- o5. Install the first row
 - Start from a straight wall and use spacers to maintain the required expansion gap around the perimeter.
 - Place the tongue or groove side according to the locking system instructions.
 - Keep the first row straight, as it will guide the rest of the installation.
- o7. Cut and fit edge planks
 - Measure carefully before cutting the last plank in each row and the final row.
 - Wear suitable protective equipment when cutting, including gloves, eye protection, and a mask.
 - Leave expansion gaps at walls, door frames, pipes, columns, cabinets, and other fixed structures.
- o9. Final checks
 - Remove spacers and check that all planks are locked properly with no visible gaps, lifted edges, or loose sections.
 - Clean installation dust with a soft broom, vacuum with hard-floor setting, or dry microfiber mop.
 - Do not wash heavily, steam-clean, or expose the floor to standing water immediately after installation.
- o2. Acclimate the flooring
 - Store SPC flooring flat in the installation area for 24–48 hours before installation.
 - Keep cartons flat and unopened where possible to protect the locking edges.
 - Maintain stable room conditions before, during, and after installation.
- o4. Plan the layout
 - Measure the room and plan the plank direction before installation.
 - Mix planks from several cartons to achieve a natural colour and pattern variation.
 - Stagger short-end joints between rows to improve appearance and stability.
 - Check door clearance, wall edges, and fixed structures before laying the first row.
- o6. Connect the planks
 - Fit the short and long edges together using the recommended click-lock method.
 - Do not force the locking system if the plank is not aligned; lift and reposition before locking.
 - Use suitable installation tools where required and avoid damaging the plank edges.
- o8. Install trims and accessories
 - Install skirting, T-moulding, L-moulding, transition strips, or edge trims as required.
 - Do not fasten trims through floating floor planks in a way that prevents natural floor movement.
 - Ensure accessories are aligned and firmly fixed according to the manufacturer's instructions.



Scan Here
for video guide

Direction of Use

- 01. Use SPC flooring only for suitable indoor residential or light commercial applications.
- 03. Keep the floor free from sand, stones, grit, sharp objects, and hard debris that may scratch the surface.
- 05. Use felt pads under furniture legs and suitable protective mats under rolling chairs, heavy appliances, and frequently moved furniture.
- 07. Use curtains, blinds, or UV protection in areas exposed to strong direct sunlight to reduce fading, discoloration, or heat-related movement.
- 02. Do not install or use SPC flooring outdoors, in open balconies, saunas, wet rooms with standing water, or areas exposed to continuous water flow.
- 04. Lift furniture and appliances when moving them. Do not drag heavy items across the floor.
- 06. Avoid placing hot items, burning materials, cigarettes, or open flames directly on the floor.

Initial Use and Early Care

- 01. Allow the flooring to settle after installation before heavy use, heavy cleaning, or moving large furniture back into place.
- 03. Maintain good ventilation during and after installation, especially when adhesives, sealants, or trims are used.
- 05. Place entrance mats at doorways immediately after installation to reduce grit and dirt being carried onto the floor.
- 02. For adhesive installation, allow the adhesive to cure fully according to the adhesive manufacturer's instructions before wet cleaning or heavy traffic.
- 04. Check the floor after installation for raised edges, gaps, damaged planks, or areas that do not lock properly.

Routine Cleaning and Maintenance

- 01. Sweep, dust-mop, or vacuum regularly using a soft broom, microfiber mop, or vacuum with a hard-floor setting.
- 03. Mop with a damp, well-wrung microfiber mop and a mild pH-neutral cleaner suitable for vinyl or SPC flooring.
- 05. For sticky marks or scuffs, use a soft cloth and manufacturer-approved cleaner. Always test cleaning products on a hidden area first.
- 07. Do not pour water directly onto the floor or allow water to pool along joints, skirting, transitions, or wall edges.
- 02. Do not use vacuums with rotating beater bars or stiff brushes that may scratch the floor surface.
- 04. Wipe spills immediately with a soft absorbent cloth to prevent staining, slipping, or moisture entering joints.
- 06. Do not use steam cleaners, excessive water, wax, polish, oil soap, abrasive powders, steel wool, bleach, ammonia, strong acids, strong alkalis, or harsh solvents.

Area-Specific Care Instructions

Area or Condition	Care Direction
01. Kitchens and dining areas	Wipe food, oil, and drink spills promptly. Use mats near sinks, stoves, and preparation areas to reduce water, grease, and grit exposure.
02. Laundry areas, and wet prone zones	Maintain ventilation, wipe splashes and condensation promptly, and do not allow standing water to remain on the floor or around edges.
03. Entrances and corridors	Use non-staining entrance mats and clean frequently to remove sand, grit, and dirt that may cause scratches or dulling.
04. Living rooms and bedrooms	Use felt pads under furniture legs and lift furniture when rearranging. Avoid dragging beds, cabinets, tables, or chairs across the floor.
05. Office or commercial use	Use chair mats under rolling chairs and protective boards when moving heavy equipment. Increase cleaning frequency in high-traffic areas.

Repair and Replacement Care

01. Keep spare planks from the same batch where possible for future repairs and colour matching.	02. For light scuffs or minor marks, clean gently with a soft cloth and manufacturer-approved cleaner.
03. For small scratches or chips, use only manufacturer-approved repair kits, touch-up solutions, or fillers suitable for SPC flooring.	04. Replace deeply scratched, cracked, swollen, lifted, or broken planks promptly to prevent further damage or unsafe walking conditions.
05. Use felt pads under furniture legs and suitable protective mats under rolling chairs, heavy appliances, and frequently moved furniture.	06. Before repair or replacement, identify and correct the cause of damage, such as moisture, uneven subfloor, dragging furniture, impact, or unsuitable cleaning products.

Repair Guide

01. Identify damaged plank • Confirm which plank needs replacement. • Inspect for cracks, chips or water damage. • Mark the damaged plank with tape.	02. Prepare the work area • Remove furniture and rugs. • Clean dust and debris around the damaged plank. • Wear gloves and safety glasses.
03. Cut and remove plank • Carefully cut the damaged plank to remove it without disturbing others. • Use a circular saw or blade set to plank thickness of ca. 4mm. • Cut two parallel lines lengthwise inside the plank. • Pry out the centre piece, then remove remaining edges with a chisel.	04. Clean floor • Ensure the exposed floor is ready for the new plank. • Remove adhesive residue or debris. • Check for moisture or unevenness. • Vacuum the area thoroughly.

- | | |
|---|--|
| <p>o5. Trim replacement plank</p> <ul style="list-style-type: none">• Modify the new plank so it can fit into the gap• Cut off the tongue and groove edges.• Dry fit without any adhesive to confirm alignment.• Ensure colour and pattern match existing floor. <p>o7. Finish and inspect</p> <ul style="list-style-type: none">• Check the repair for stability and appearance.• Wipe away excess adhesive• Ensure the plank is level with surrounding floor.• Allow 24 hours before heavy use. | <p>o6. Install new plank</p> <ul style="list-style-type: none">• Secure the replacement plank in place.• Apply flooring adhesive to the floor• Place plank into the gap and press firmly.• Use a weighted object to hold it flat during curing. |
|---|--|

Safety Precautions

- | | |
|---|--|
| <p>o1. Read and follow the product label, installation guide, technical data sheet, and safety instructions before installation or use.</p> <p>o3. Wear suitable protective equipment when cutting or installing planks, including gloves, eye protection, and a mask.</p> <p>o5. Ensure good ventilation when using adhesives, sealants, or cleaning products.</p> | <p>o2. Keep planks, packaging materials, cutting tools, adhesives, spacers, trims, and small parts away from children and pets.</p> <p>o4. Use cutting tools carefully and cut planks in a safe, stable, and well-ventilated area.</p> <p>o6. Do not use damaged flooring areas that are lifted, loose, slippery, cracked, or unstable until repaired.</p> |
|---|--|

Storage, Handling, and Disposal

- | | |
|--|---|
| <p>o1. Store SPC flooring flat in its original packaging on a clean, dry, level, and supported surface.</p> <p>o3. Do not store cartons upright, on their sides, or in areas where locking edges may be damaged.</p> <p>o5. Dispose of offcuts, damaged planks, packaging, adhesives, and installation waste according to local regulations.</p> | <p>o2. Keep flooring in a cool, dry, shaded, and well-ventilated area away from direct sunlight, moisture, leaks, and extreme temperatures.</p> <p>o4. Handle planks carefully to avoid chipping corners, breaking locking profiles, or scratching the surface.</p> <p>o6. Do not burn SPC flooring or dispose of installation waste in an unsafe manner.</p> |
|--|---|

Warranty and Customer Care Reminder

SPC flooring performance may be affected by improper installation, unsuitable subfloor conditions, excessive moisture, standing water, poor ventilation, direct heat, heavy impact, dragging furniture, harsh cleaning products, abrasive tools, unauthorized modification, or lack of reasonable maintenance. Damage or failure caused by these conditions may not be covered under warranty. Customers should follow the product label, installation guide, technical data sheet, safety information, and any manufacturer-specific care guidance supplied with the flooring.

Quick SPC L Moulding Care Checklist

01. Inspect planks before installation.

03. Prepare a clean, dry, level, and stable subfloor.

05. Sweep or vacuum regularly using soft hard-floor tools.

07. Wipe spills immediately and avoid standing water.

09. Use entrance mats, felt pads, and chair mats to protect the floor.
02. Acclimate and store planks flat before installation.

04. Maintain correct expansion gaps around walls and fixed structures.

06. Damp mop only with a mild pH-neutral cleaner.

08. Do not use steam cleaners, wax, polish, abrasive pads, bleach, ammonia, or harsh solvents.

10. Repair or replace damaged planks promptly and keep spare planks for future matching.

Skirting

BP0007B

Specification

Width Length Height
2400mm × 90mm × 12mm

25 pcs/ ctn

Pending
image



Installation Guide

- o1. Check the product and site condition
 - Inspect all cartons and planks before installation. Do not install damaged, warped, chipped, or visibly defective planks.
 - Confirm the colour, design, batch, and quantity before starting work.
 - Ensure the room is enclosed, dry, clean, and suitable for indoor flooring installation.
- o3. Acclimate the flooring
 - Ensure the subfloor is clean, dry, level, stable, and free from dust, grease, wax, adhesive residue, nails, debris, and loose particles.
 - Repair cracks, holes, high spots, low spots, or uneven areas using suitable patching or levelling material.
 - Concrete subfloors must be properly cured and dry before installation.
 - Do not install over soft, unstable, damp, mouldy, or uneven surfaces.
- o5. Install the first row
 - Start from a straight wall and use spacers to maintain the required expansion gap around the perimeter.
 - Place the tongue or groove side according to the locking system instructions.
 - Keep the first row straight, as it will guide the rest of the installation.
- o7. Cut and fit edge planks
 - Measure carefully before cutting the last plank in each row and the final row.
 - Wear suitable protective equipment when cutting, including gloves, eye protection, and a mask.
 - Leave expansion gaps at walls, door frames, pipes, columns, cabinets, and other fixed structures.
- o9. Final checks
 - Remove spacers and check that all planks are locked properly with no visible gaps, lifted edges, or loose sections.
 - Clean installation dust with a soft broom, vacuum with hard-floor setting, or dry microfiber mop.
 - Do not wash heavily, steam-clean, or expose the floor to standing water immediately after installation.
- o2. Acclimate the flooring
 - Store SPC flooring flat in the installation area for 24–48 hours before installation.
 - Keep cartons flat and unopened where possible to protect the locking edges.
 - Maintain stable room conditions before, during, and after installation.
- o4. Plan the layout
 - Measure the room and plan the plank direction before installation.
 - Mix planks from several cartons to achieve a natural colour and pattern variation.
 - Stagger short-end joints between rows to improve appearance and stability.
 - Check door clearance, wall edges, and fixed structures before laying the first row.
- o6. Connect the planks
 - Fit the short and long edges together using the recommended click-lock method.
 - Do not force the locking system if the plank is not aligned; lift and reposition before locking.
 - Use suitable installation tools where required and avoid damaging the plank edges.
- o8. Install trims and accessories
 - Install skirting, T-moulding, L-moulding, transition strips, or edge trims as required.
 - Do not fasten trims through floating floor planks in a way that prevents natural floor movement.
 - Ensure accessories are aligned and firmly fixed according to the manufacturer's instructions.



Scan Here
for video guide

Direction of Use

- 01. Use SPC flooring only for suitable indoor residential or light commercial applications.
- 03. Keep the floor free from sand, stones, grit, sharp objects, and hard debris that may scratch the surface.
- 05. Use felt pads under furniture legs and suitable protective mats under rolling chairs, heavy appliances, and frequently moved furniture.
- 07. Use curtains, blinds, or UV protection in areas exposed to strong direct sunlight to reduce fading, discoloration, or heat-related movement.
- 02. Do not install or use SPC flooring outdoors, in open balconies, saunas, wet rooms with standing water, or areas exposed to continuous water flow.
- 04. Lift furniture and appliances when moving them. Do not drag heavy items across the floor.
- 06. Avoid placing hot items, burning materials, cigarettes, or open flames directly on the floor.

Initial Use and Early Care

- 01. Allow the flooring to settle after installation before heavy use, heavy cleaning, or moving large furniture back into place.
- 03. Maintain good ventilation during and after installation, especially when adhesives, sealants, or trims are used.
- 05. Place entrance mats at doorways immediately after installation to reduce grit and dirt being carried onto the floor.
- 02. For adhesive installation, allow the adhesive to cure fully according to the adhesive manufacturer's instructions before wet cleaning or heavy traffic.
- 04. Check the floor after installation for raised edges, gaps, damaged planks, or areas that do not lock properly.

Routine Cleaning and Maintenance

- 01. Sweep, dust-mop, or vacuum regularly using a soft broom, microfiber mop, or vacuum with a hard-floor setting.
- 03. Mop with a damp, well-wrung microfiber mop and a mild pH-neutral cleaner suitable for vinyl or SPC flooring.
- 05. For sticky marks or scuffs, use a soft cloth and manufacturer-approved cleaner. Always test cleaning products on a hidden area first.
- 07. Do not pour water directly onto the floor or allow water to pool along joints, skirting, transitions, or wall edges.
- 02. Do not use vacuums with rotating beater bars or stiff brushes that may scratch the floor surface.
- 04. Wipe spills immediately with a soft absorbent cloth to prevent staining, slipping, or moisture entering joints.
- 06. Do not use steam cleaners, excessive water, wax, polish, oil soap, abrasive powders, steel wool, bleach, ammonia, strong acids, strong alkalis, or harsh solvents.

Area-Specific Care Instructions

Area or Condition	Care Direction
01. Kitchens and dining areas	Wipe food, oil, and drink spills promptly. Use mats near sinks, stoves, and preparation areas to reduce water, grease, and grit exposure.
02. Laundry areas, and wet prone zones	Maintain ventilation, wipe splashes and condensation promptly, and do not allow standing water to remain on the floor or around edges.
03. Entrances and corridors	Use non-staining entrance mats and clean frequently to remove sand, grit, and dirt that may cause scratches or dulling.
04. Living rooms and bedrooms	Use felt pads under furniture legs and lift furniture when rearranging. Avoid dragging beds, cabinets, tables, or chairs across the floor.
05. Office or commercial use	Use chair mats under rolling chairs and protective boards when moving heavy equipment. Increase cleaning frequency in high-traffic areas.

Repair and Replacement Care

01. Keep spare planks from the same batch where possible for future repairs and colour matching.	02. For light scuffs or minor marks, clean gently with a soft cloth and manufacturer-approved cleaner.
03. For small scratches or chips, use only manufacturer-approved repair kits, touch-up solutions, or fillers suitable for SPC flooring.	04. Replace deeply scratched, cracked, swollen, lifted, or broken planks promptly to prevent further damage or unsafe walking conditions.
05. Use felt pads under furniture legs and suitable protective mats under rolling chairs, heavy appliances, and frequently moved furniture.	06. Before repair or replacement, identify and correct the cause of damage, such as moisture, uneven subfloor, dragging furniture, impact, or unsuitable cleaning products.

Repair Guide

01. Identify damaged plank • Confirm which plank needs replacement. • Inspect for cracks, chips or water damage. • Mark the damaged plank with tape.	02. Prepare the work area • Remove furniture and rugs. • Clean dust and debris around the damaged plank. • Wear gloves and safety glasses.
03. Cut and remove plank • Carefully cut the damaged plank to remove it without disturbing others. • Use a circular saw or blade set to plank thickness of ca. 4mm. • Cut two parallel lines lengthwise inside the plank. • Pry out the centre piece, then remove remaining edges with a chisel.	04. Clean floor • Ensure the exposed floor is ready for the new plank. • Remove adhesive residue or debris. • Check for moisture or unevenness. • Vacuum the area thoroughly.

- | | |
|---|---|
| <p>o5. Trim replacement plank</p> <ul style="list-style-type: none"> • Modify the new plank so it can fit into the gap • Cut off the tongue and groove edges. • Dry fit without any adhesive to confirm alignment. • Ensure colour and pattern match existing floor. <p>o7. Finish and inspect</p> <ul style="list-style-type: none"> • Check the repair for stability and appearance. • Wipe away excess adhesive • Ensure the plank is level with surrounding floor. • Allow 24 hours before heavy use. | <p>o6. Install new plank</p> <ul style="list-style-type: none"> • Secure the replacement plank in place. • Apply flooring adhesive to the floor • Place plank into the gap and press firmly. • Use a weighted object to hold it flat during curing. |
|---|---|

Safety Precautions

- | | |
|---|--|
| <p>o1. Read and follow the product label, installation guide, technical data sheet, and safety instructions before installation or use.</p> <p>o3. Wear suitable protective equipment when cutting or installing planks, including gloves, eye protection, and a mask.</p> <p>o5. Ensure good ventilation when using adhesives, sealants, or cleaning products.</p> | <p>o2. Keep planks, packaging materials, cutting tools, adhesives, spacers, trims, and small parts away from children and pets.</p> <p>o4. Use cutting tools carefully and cut planks in a safe, stable, and well-ventilated area.</p> <p>o6. Do not use damaged flooring areas that are lifted, loose, slippery, cracked, or unstable until repaired.</p> |
|---|--|

Storage, Handling, and Disposal

- | | |
|--|---|
| <p>o1. Store SPC flooring flat in its original packaging on a clean, dry, level, and supported surface.</p> <p>o3. Do not store cartons upright, on their sides, or in areas where locking edges may be damaged.</p> <p>o5. Dispose of offcuts, damaged planks, packaging, adhesives, and installation waste according to local regulations.</p> | <p>o2. Keep flooring in a cool, dry, shaded, and well-ventilated area away from direct sunlight, moisture, leaks, and extreme temperatures.</p> <p>o4. Handle planks carefully to avoid chipping corners, breaking locking profiles, or scratching the surface.</p> <p>o6. Do not burn SPC flooring or dispose of installation waste in an unsafe manner.</p> |
|--|---|

Warranty and Customer Care Reminder

SPC flooring performance may be affected by improper installation, unsuitable subfloor conditions, excessive moisture, standing water, poor ventilation, direct heat, heavy impact, dragging furniture, harsh cleaning products, abrasive tools, unauthorized modification, or lack of reasonable maintenance. Damage or failure caused by these conditions may not be covered under warranty. Customers should follow the product label, installation guide, technical data sheet, safety information, and any manufacturer-specific care guidance supplied with the flooring.

Quick Skirting Care Checklist

- 01. Inspect planks before installation.
- 02. Acclimate and store planks flat before installation.
- 03. Prepare a clean, dry, level, and stable subfloor.
- 04. Maintain correct expansion gaps around walls and fixed structures.
- 05. Sweep or vacuum regularly using soft hard-floor tools.
- 06. Damp mop only with a mild pH-neutral cleaner.
- 07. Wipe spills immediately and avoid standing water.
- 08. Do not use steam cleaners, wax, polish, abrasive pads, bleach, ammonia, or harsh solvents.
- 09. Use entrance mats, felt pads, and chair mats to protect the floor.
- 10. Repair or replace damaged planks promptly and keep spare planks for future matching.

Wainscoting

BP0007A

Specification

Width Length Height
2400mm × 24mm × 12mm

128 pcs/ ctn

Pending
image



Installation Guide

01. Check the product and wall condition
 - Inspect all panels, trims, mouldings, rails, skirting, and accessories before installation.
 - Do not install panels that are cracked, warped, swollen, chipped, bent, mouldy, or visibly defective.
 - Confirm the colour, design, profile, batch, quantity, and installation layout before starting work.
 - Ensure the installation area is indoors, dry, clean, and suitable for decorative wall finishing.
03. Prepare the wall surface
 - Ensure the wall is clean, dry, flat, stable, and free from dust, grease, loose paint, wallpaper residue, mould, dampness, and loose particles.
 - Repair cracks, holes, uneven areas, or weak surfaces before installation.
 - Do not install over wet, powdery, peeling, unstable, or mouldy walls.
 - Identify and fix water leakage, seepage, condensation, or rising damp before installing panels.
05. Cut and dry-fit components
 - Cut panels, rails, mouldings, and trims using suitable tools e.g. a saw or a fine blade to reduce chipping.
 - Dry-fit all parts before final fixing to confirm alignment, spacing, height, and corner joints.
 - Make accurate cut-outs for sockets, switches, skirting, door frames, pipes, or other wall features.
 - Wear suitable protective equipment when cutting, including gloves, eye protection, and a mask.
07. Cut and fit edge planks
 - Check that all panels, trims, rails, and mouldings are secure, straight, flush, and properly aligned.
 - Remove installation dust using a soft cloth, microfiber duster, or vacuum with a soft brush attachment.
 - Do not wash heavily, scrub, or expose the finished wall to moisture immediately after installation.
02. Acclimate the panels
 - Store SPC panels flat in the installation area for 24–48 hours before installation.
 - Keep products away from rain, leaks, direct sunlight, and excessive humidity during acclimation.
 - Maintain stable room conditions before, during, and after installation.
04. Plan and mark the layout
 - Measure the wall width and height carefully before cutting or fixing any panel.
 - Mark level guide lines for the base, top rail, vertical stiles, panel spacing, and decorative mouldings.
 - Plan panel spacing symmetrically around doors, windows, corners, switches, sockets, and fixed furniture.
 - Check that the layout is straight, level, and visually balanced before applying adhesive or fasteners.
06. Fix the base, panels, and trims
 - Apply suitable construction adhesive or recommended fixing method to the back of panels and trims.
 - Press each piece firmly into position and check level, plumb, and alignment continuously.



Scan Here
for video guide

Direction of Use

- 01. Use wainscoting wall decorative finishing only for suitable indoor wall applications.
- 02. Do not use panels as structural support, shelving support, climbing support, or load-bearing material.
- 03. Do not hang heavy objects directly from panels unless the fixing is anchored properly into wall studs or suitable wall plugs.
- 04. Keep the wall finish away from direct water spray, standing water, active leaks, excessive heat, open flames, and prolonged direct sunlight.
- 05. Avoid impact from furniture, appliances, trolleys, doors, sharp objects, or heavy items.
- 06. Use door stops, furniture pads, or protective bumpers where furniture or doors may contact the wall finish.
- 07. Maintain good room ventilation, especially in humid areas, to reduce condensation, mould, swelling, or paint failure.

Initial Use and Early Care

- 01. Allow adhesive, caulk, filler, primer, paint, stain, or sealant to dry and cure fully before wiping, decorating, or placing furniture close to the wall.
- 02. Avoid heavy cleaning or scrubbing during the early curing period.
- 03. Keep newly installed panels dry and well ventilated.
- 04. Inspect joints, edges, trims, and corners after installation for gaps, loose sections, uneven alignment, or visible movement.

Routine Cleaning and Maintenance

- 01. Dust regularly using a clean, soft, dry cloth, microfiber duster, or vacuum with a soft brush attachment.
- 02. For light marks, wipe gently with a soft cloth slightly dampened with clean water, then dry immediately.
- 03. For tougher dirt, use a mild soap solution and a soft non-abrasive cloth, then wipe with clean water and dry.
- 04. Clean grooves, moulding profiles, corners, and ledges carefully to prevent dust build-up.
- 05. Do not soak, spray heavily, pressure-wash, steam-clean, or allow water to remain on panel joints, edges, or trims.
- 06. Avoid abrasive pads, steel wool, bleach, ammonia, strong acids, strong alkalis, harsh solvents, alcohol-based cleaners, and heavy-duty cleaners unless specifically approved for the finish.
- 07. Always test any cleaning product on a hidden area before applying it to visible surfaces.

Repair and Touch-Up Care

- 01. Repair light scuffs, small chips, nail holes, or minor paint marks using suitable filler, touch-up paint, stain, or repair material.
- 02. Before repair, clean and dry the affected area and remove loose paint, dust, or damaged material.
- 03. Use the same paint colour, finish, and application method where possible to reduce visible differences.
- 04. Re-caulk or reseal gaps at joints, corners, trims, or edges if separation occurs after settlement or humidity changes.
- 05. Replace panels or mouldings that are deeply cracked, swollen, warped, detached, mouldy, or structurally damaged.
- 06. Identify and correct the cause of repeated damage, such as moisture, impact, poor adhesion, uneven wall surfaces, or unsuitable cleaning products.

Safety Precautions

01.

Read and follow the product label, installation guide before installation or use.
02.

Keep packaging materials, plastic bags, sharp offcuts, nails, screws, adhesives, sealants, and small parts away from children and pets.
03.

Wear suitable protective equipment during installation, including gloves, eye protection, and a mask when cutting or sanding.
04.

Use cutting tools, nail guns, drills, and ladders safely and only on stable surfaces.
05.

Switch off electrical power and seek qualified assistance when working near sockets, switches, concealed wiring, or electrical fixtures.
06.

Ensure good ventilation when using adhesives, sealants, primers, paints, or cleaning products.
07.

Dispose of offcuts, packaging, adhesives, sealants, paint waste, and damaged panels according to local regulations.

Storage, Handling, and Disposal

01.

Store panels, trims, mouldings, rails, and accessories flat in their original packaging on a clean, dry, level, and supported surface.
02.

Keep products away from damp walls, wet floors, leaks, direct sunlight, high heat, and extreme humidity.
03.

Do not store panels upright, leaning heavily, or under excessive weight, as this may cause bending, warping, or edge damage.
04.

Handle panels carefully to avoid chipping corners, denting profiles, scratching painted surfaces, or damaging decorative edges.
05.

Store leftover materials sealed, labelled, and away from children, pets, heat, and flames.
06.

Dispose of offcuts, packaging, adhesives, sealants, paint waste, and damaged panels according to local regulations.

Warranty and Customer Care Reminder

Wainscoting wall decorative finishing performance may be affected by improper installation, unsuitable wall condition, excessive moisture, active leaks, poor ventilation, uneven surfaces, incorrect adhesive or fasteners, insufficient drying time, heavy impact, harsh cleaning products, unauthorized modification, or lack of reasonable maintenance. Damage or failure caused by these conditions may not be covered under warranty. Customers should follow the product label, installation guide, adhesive instructions, finishing instructions, safety information, and any manufacturer-specific care guidance supplied with the product.

Quick Wainscoting Care Checklist

01.

Inspect panels, trims, and accessories before installation.
02.

Acclimate panels in the installation area before fixing.
03.

Prepare a clean, dry, flat, and stable wall surface.
04.

Measure, mark, and dry-fit the layout before applying adhesive or fasteners.
05.

Use suitable adhesive
06.

Allow adhesive to dry and cure before heavy cleaning or use.
07.

Dust regularly and clean gently with a soft cloth.
08.

Wipe moisture, splashes, and condensation promptly.
09.

Avoid soaking, steam-cleaning, abrasive pads, bleach, harsh solvents, and heavy scrubbing.
10.

Repair loose joints, gaps, chips, scuffs, or damaged panels promptly.

Stay Longer Interior Paint

BPooo6-XXXX Pure White
BPooo6-XXXX Pale Dusk
BPooo6-XXXX Ash Grey

Stay Longer Interior Paint is developed to be low odour, easy to clean, durable, and finished with a subtle pearl texture. Instead of offering countless colours and finishes, we carefully curated three timeless shades (Pure White, Ash Grey, and Pale Dusk) to help you create a home interior that stays timeless.

Pending
product
code

Specification

5L / 15L



Installation Guide



Scan Here
for video guide

01. Application Guide

 - Proper preparation ensures adhesion and durability.
 - Clean walls of dust, grease, and loose particles.
 - Remove flaking paint or wallpaper adhesive
 - Repair cracks or holes with filler and sand smooth.
 - Ensure the surface is dry and free from dampness.
03. Check sealer dryness

 - Confirm the surface is stable before painting.
 - The surface should feel dry and not tacky to touch.
 - If the surface is powdery or uneven, apply a second coat.
 - Maintain good ventilation during drying.
05. After care and curing

 - Proper after care extends the life of the finish.
 - Avoid washing or scrubbing freshly painted walls for at least 7 days.
 - Keep surfaces dry during curing.
 - Repair leaks or dampness promptly.
 - Use gently cleaning methods once fully cured.
02. Apply interior sealer

 - Sealer binds porous or powdery surfaces before painting.
 - Stir sealer thoroughly before use.
 - Apply evenly with a brush or roller.
 - Avoid puddles or thick patches.
 - Allow recommended drying time of at least 1 hour.
04. Apply interior paint

 - Stir paint well before use.
 - Apply with roller or brush in thin, even coats.
 - Allow at least 1 hour drying between coats.
 - Apply 2 coats for best coverage.

Directions of Use and Application

01. Use interior paint only for suitable indoor wall, ceiling, trim, or surface applications as recommended on the product label.

03. Apply paint using suitable tools such as a clean brush, roller, or spray equipment according to the product instructions.

05. Apply the recommended number of coats and allow sufficient drying time between coats.
02. Stir the paint thoroughly before use to ensure even colour, sheen, and consistency.

04. Ensure the area is well ventilated during painting and drying.

06. Do not apply paint on wet, dusty, oily, mouldy, peeling, or unstable surfaces.

Surface Preparation Before Painting

01. Clean the surface to remove dust, dirt, grease, stains, chalking, and loose particles before painting.

03. Remove peeling or flaking paint and ensure the remaining surface is sound and firmly attached.

05. Use a suitable primer or sealer where required, especially on porous, stained, repaired, or previously unpainted surfaces.
02. Repair cracks, holes, uneven areas, and surface defects using suitable filler or patching compound, then sand smooth when dry.

04. Allow newly plastered, skim-coated, or damp surfaces to dry completely before painting.

06. Protect floors, furniture, fixtures, switches, sockets, doors, windows, and fittings from splashes using suitable coverings or masking tape.

Drying, Curing, and Early Care

- 01. Allow painted surfaces to dry according to the product label before touching, recoating, cleaning, or placing items against the wall.
- 02. Drying time may vary depending on paint type, surface condition, temperature, humidity, ventilation, and coat thickness.
- 03. Avoid washing or scrubbing newly painted surfaces until the coating has cured sufficiently.
- 04. Keep furniture, decorations, tape, hooks, and other objects away from freshly painted surfaces during the early curing period.
- 05. Maintain good ventilation after painting to help reduce odour and support proper drying.
- 06. Avoid exposing freshly painted surfaces to excessive moisture, steam, condensation, or heavy cleaning too soon after application.

Surface and Finish-Specific Care Instructions

Surface or Condition	Use and Care Direction
01. New plaster, skim coat, or cement surface	Allow the surface to dry and cure properly before sealing. Use sealer to reduce excessive absorption and improve the consistency of the finishing coat.
02. Powdery or chalky surface	Remove loose powder as much as possible before sealing. Apply sealer to help bind the surface and improve adhesion for the next coating.
03. Repaired or patched wall area	Sand the repaired area smooth and remove dust before sealing. Sealer helps reduce uneven absorption and visible patch marks after painting.
04. Old painted surface	Ensure old paint is firmly attached. Remove peeling or loose paint before sealing or repainting.
05. Wallpaper adhesive residue	Remove heavy adhesive build-up and clean the surface before sealing. Sealer can help lock down remaining residue where suitable.
06. Damp or stained surface	Identify and fix the source of moisture or staining before sealing. Do not apply sealer over active leaks, rising damp, or wet surfaces.

Paint Finish or Area	Care Direction
01. Flat or matte finish	Clean very gently using minimal water and light pressure. Avoid scrubbing, as flat finishes may show shiny marks or surface wear more easily.
02. Eggshell, satin, or low-sheen finish	Clean with a soft damp cloth and mild soap when needed. Use gentle pressure and dry the area after cleaning.
03. Semi-gloss or gloss finish	Generally easier to wipe clean. Use mild cleaner and a soft cloth, then rinse and dry. Avoid abrasive tools that may scratch the surface.
04. Kitchen, bathroom, or high-humidity area	Maintain good ventilation to reduce moisture, steam, mould, and peeling. Wipe condensation and splashes promptly.
05. High-traffic walls, corridors, and children's rooms	Clean marks promptly with mild methods. Use touch-up paint when cleaning cannot remove scuffs or chips without damaging the finish.

Touch-Up, Repair, and Repainting Care

- 01. Keep a small amount of leftover paint in a sealed container for future touch-ups where permitted.
- 02. Label stored paint with the colour name, colour code, room location, finish, batch number, and date of application.
- 03. Before touch-up, clean and dry the affected area and lightly sand rough edges where necessary.
- 04. Use the same paint type, colour, sheen, and application method whenever possible to reduce visible differences.
- 05. Feather touch-up paint lightly into the surrounding area instead of applying a heavy patch.
- 06. For large stains, peeling, uneven colour, water damage, or repeated mould growth, identify and correct the underlying cause before repainting.

Safety Precautions

- 01. Read and follow the product label, safety instructions, and technical information before use.
- 02. Keep paint, thinner, cleaning liquids, tools, and packaging away from children and pets.
- 03. Wear suitable protective equipment such as gloves, eye protection, and a mask or respirator where recommended.
- 04. Ensure good ventilation during painting, drying, and clean-up.
- 05. Keep paint away from open flames, sparks, heat sources, and smoking areas, especially when using solvent-based products.
- 06. In case of skin or eye contact, rinse immediately with clean water and seek medical advice if irritation continues.

Storage, Handling, and Disposal

- 01. Store paint in its original container with the lid tightly closed.
- 02. Keep paint in a cool, dry, well-ventilated place away from direct sunlight, heat, sparks, freezing conditions, and moisture.
- 03. Do not mix paint with other chemicals, cleaners, solvents, or unknown products.
- 04. Prevent paint from entering drains, soil, waterways, or household wastewater systems.
- 05. Dispose of unused paint, empty containers, contaminated cloths, and cleaning waste according to local regulations and product label instructions.
- 06. Clean tools promptly after use using the recommended cleaning method for the paint type.

Warranty and Customer Care Reminder

Paint performance may be affected by improper surface preparation, unsuitable primer, excessive moisture, poor ventilation, incompatible substrates, incorrect application, insufficient drying time, harsh cleaning, water leakage, mould, or structural defects. Damage or failure caused by these conditions may not be covered under warranty. Customers should follow the product label, colour card, technical data sheet, safety information, and any manufacturer-specific guidance.

Quick Interior Paint Care Checklist

- o1. Prepare and clean the surface before painting.
 - o2. Stir paint thoroughly and apply with suitable tools.
 - o3. Ensure good ventilation during application and drying.
 - o4. Allow proper drying and curing time before cleaning or placing items against painted surfaces.
 - o5. Dust regularly and clean gently with water or mild soap solution.
 - o6. Avoid harsh chemicals, abrasive pads, and heavy scrubbing.
 - o7. Dust regularly and clean gently with a soft cloth.
 - o8. Store leftover paint sealed, labelled, and away from heat, sunlight, children, and pets.
-

Stay Longer Interior Sealer

BPooo6S-5L

Interior sealer is used as a protective coating applied to the frame's internal wood, helping guard against moisture, pests, and warping over time.

Specification

5L



Installation Guide



Scan Here
for video guide

01. Application Guide
 - Proper preparation ensures adhesion and durability.
 - Clean walls of dust, grease, and loose particles.
 - Remove flaking paint or wallpaper adhesive
 - Repair cracks or holes with filler and sand smooth.
 - Ensure the surface is dry and free from dampness.
03. Check sealer dryness
 - Confirm the surface is stable before painting.
 - The surface should feel dry and not tacky to touch.
 - If the surface is powdery or uneven, apply a second coat.
 - Maintain good ventilation during drying.
05. After care and curing
 - Proper after care extends the life of the finish.
 - Avoid washing or scrubbing freshly painted walls for at least 7 days.
 - Keep surfaces dry during curing.
 - Repair leaks or dampness promptly.
 - Use gently cleaning methods once fully cured.
02. Apply interior sealer
 - Sealer binds porous or powdery surfaces before painting.
 - Stir sealer thoroughly before use.
 - Apply evenly with a brush or roller.
 - Avoid puddles or thick patches.
 - Allow recommended drying time of at least 1 hour.
04. Apply interior paint
 - Stir paint well before use.
 - Apply with roller or brush in thin, even coats.
 - Allow at least 1 hour drying between coats.
 - Apply 2 coats for best coverage.

Directions of Use and Application

01. Use interior paint only for suitable indoor wall, ceiling, trim, or surface applications as recommended on the product label.
03. Apply paint using suitable tools such as a clean brush, roller, or spray equipment according to the product instructions.
05. Apply the recommended number of coats and allow sufficient drying time between coats.
02. Stir the paint thoroughly before use to ensure even colour, sheen, and consistency.
04. Ensure the area is well ventilated during painting and drying.
06. Do not apply paint on wet, dusty, oily, mouldy, peeling, or unstable surfaces.

Surface Preparation Before Painting

01. Clean the surface to remove dust, dirt, grease, stains, chalking, and loose particles before painting.
03. Remove peeling or flaking paint and ensure the remaining surface is sound and firmly attached.
05. Use a suitable primer or sealer where required, especially on porous, stained, repaired, or previously unpainted surfaces.
02. Repair cracks, holes, uneven areas, and surface defects using suitable filler or patching compound, then sand smooth when dry.
04. Ensure the area is well ventilated during painting and drying.
06. Allow newly plastered, skim-coated, or damp surfaces to dry completely before painting.
06. Protect floors, furniture, fixtures, switches, sockets, doors, windows, and fittings from splashes using suitable

Drying, Curing, and Early Care

01. Allow painted surfaces to dry according to the product label before touching, recoating, cleaning, or placing items against the wall.

03. Avoid washing or scrubbing newly painted surfaces until the coating has cured sufficiently.

05. Maintain good ventilation after painting to help reduce odour and support proper drying.
02. Drying time may vary depending on paint type, surface condition, temperature, humidity, ventilation, and coat thickness.

04. Keep furniture, decorations, tape, hooks, and other objects away from freshly painted surfaces during the early curing period.

06. Avoid exposing freshly painted surfaces to excessive moisture, steam, condensation, or heavy cleaning too soon after application.

Surface and Finish-Specific Care Instructions

Surface or Condition	Use and Care Direction
01. New plaster, skim coat, or cement surface	Allow the surface to dry and cure properly before sealing. Use sealer to reduce excessive absorption and improve the consistency of the finishing coat.
02. Powdery or chalky surface	Remove loose powder as much as possible before sealing. Apply sealer to help bind the surface and improve adhesion for the next coating.
03. Repaired or patched wall area	Sand the repaired area smooth and remove dust before sealing. Sealer helps reduce uneven absorption and visible patch marks after painting.
04. Old painted surface	Ensure old paint is firmly attached. Remove peeling or loose paint before sealing or repainting.
05. Wallpaper adhesive residue	Remove heavy adhesive build-up and clean the surface before sealing. Sealer can help lock down remaining residue where suitable.
06. Damp or stained surface	Identify and fix the source of moisture or staining before sealing. Do not apply sealer over active leaks, rising damp, or wet surfaces.

Paint Finish or Area	Care Direction
01. Flat or matte finish	Clean very gently using minimal water and light pressure. Avoid scrubbing, as flat finishes may show shiny marks or surface wear more easily.
02. Eggshell, satin, or low-sheen finish	Clean with a soft damp cloth and mild soap when needed. Use gentle pressure and dry the area after cleaning.
03. Semi-gloss or gloss finish	Generally easier to wipe clean. Use mild cleaner and a soft cloth, then rinse and dry. Avoid abrasive tools that may scratch the surface.
04. Kitchen, bathroom, or high-humidity area	Maintain good ventilation to reduce moisture, steam, mould, and peeling. Wipe condensation and splashes promptly.
05. High-traffic walls, corridors, and children's rooms	Clean marks promptly with mild methods. Use touch-up paint when cleaning cannot remove scuffs or chips without damaging the finish.

Touch-Up, Repair, and Repainting Care

- 01. Keep a small amount of leftover paint in a sealed container for future touch-ups where permitted.
- 02. Label stored paint with the colour name, colour code, room location, finish, batch number, and date of application.
- 03. Before touch-up, clean and dry the affected area and lightly sand rough edges where necessary.
- 04. Use the same paint type, colour, sheen, and application method whenever possible to reduce visible differences.
- 05. Feather touch-up paint lightly into the surrounding area instead of applying a heavy patch.
- 06. For large stains, peeling, uneven colour, water damage, or repeated mould growth, identify and correct the underlying cause before repainting.

Safety Precautions

- 01. Read and follow the product label, safety instructions, and technical information before use.
- 02. Keep paint, thinner, cleaning liquids, tools, and packaging away from children and pets.
- 03. Wear suitable protective equipment such as gloves, eye protection, and a mask or respirator where recommended.
- 04. Ensure good ventilation during painting, drying, and clean-up.
- 05. Keep paint away from open flames, sparks, heat sources, and smoking areas, especially when using solvent-based products.
- 06. In case of skin or eye contact, rinse immediately with clean water and seek medical advice if irritation continues.

Storage, Handling, and Disposal

- 01. Store paint in its original container with the lid tightly closed.
- 02. Keep paint in a cool, dry, well-ventilated place away from direct sunlight, heat, sparks, freezing conditions, and moisture.
- 03. Do not mix paint with other chemicals, cleaners, solvents, or unknown products.
- 04. Prevent paint from entering drains, soil, waterways, or household wastewater systems.
- 05. Dispose of unused paint, empty containers, contaminated cloths, and cleaning waste according to local regulations and product label instructions.
- 06. Clean tools promptly after use using the recommended cleaning method for the paint type.

Warranty and Customer Care Reminder

Paint performance may be affected by improper surface preparation, unsuitable primer, excessive moisture, poor ventilation, incompatible substrates, incorrect application, insufficient drying time, harsh cleaning, water leakage, mould, or structural defects. Damage or failure caused by these conditions may not be covered under warranty. Customers should follow the product label, colour card, technical data sheet, safety information, and any manufacturer-specific guidance.

Quick Interior Sealer Care Checklist

- 01. Prepare and clean the surface before painting.
- 02. Stir paint thoroughly and apply with suitable tools.
- 03. Ensure good ventilation during application and drying.
- 04. Allow proper drying and curing time before cleaning or placing items against painted surfaces.
- 05. Dust regularly and clean gently with water or mild soap solution.
- 06. Avoid harsh chemicals, abrasive pads, and heavy scrubbing.
- 07. Dust regularly and clean gently with a soft cloth.
- 08. Store leftover paint sealed, labelled, and away from heat, sunlight, children, and pets.

bersama project

bersamaproject.com.my